

Technical Data Sheet
LAMINATED FRONTLIT

Item	G006	G007	G008	G010
Weight (g/m ²) *	300± 10	340± 10	380± 10	440± 10
Breaking Strength (N/5cm) *	497/301	497/301	650/502	850/750
Tearing Strength (N) *	85/65	85/65	115/105	185/135
Adhension (N/5cm) *	60	60	60	60
Width	up to 350cm			
FR Certification	M2, B1, B2, DIN75200, NFPA 701			
Lacquering	Acrylic or PVDF			
Cd%, Pb%, As%, Ba%, Cr%, Hg%, Se%	EN71-3			
Features	Laminated frontlit for large billboards, banners and indoor or outdoor sign with silk and wide format digital printing			

* Test method: DIN53352 BS3424

Item	G011	G012
Weight (g/m ²) *	440± 10	610± 10
Breaking Strength (N/5cm) *	1350/1200	2100/1350
Tearing Strength (N) *	245/185	400/300
Adhension (N/5cm) *	60	60
Width	up to 350cm	
FR Certification	M2, B1, B2, DIN75200, NFPA 701	
Lacquering	Acrylic or PVDF	
Cd%, Pb%, As%, Ba%, Cr%, Hg%, Se%	EN71-3	
Features	Laminated frontlit for large billboards, banners and indoor or outdoor sign with silk and wide format digital printing	

* Test method: DIN53352 BS3424